

3590EXT3GD

3590E "ENTERPRISE" 3GD series: WEIGHT INDICATOR FOR ADVANCED APPLICATIONS IN ATEX 2 & 22 ZONES



Weight indicator for ATEX areas classified at risk of explosion with protection methods according to

ATEX II 3G Ex nR IIC T6 Gc X for gases

ATEX II 3D Ex tc IIIC T85°C Dc IP68 X for dust.

The wide range of available software program guarantees the maximum versatility. Completely programmable printouts and fitted with alibi memory. CE-M approvable (OIML R-76 / EN 45501).



Working in cooperation with:

PT. INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953
 interscale@yahoo.com

The best solution
 for advanced
 industrial
 applications

MAIN FEATURES

- 25-key alphanumeric waterproof keyboard.
- Highly efficient red LED display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Easy to clean STAINLESS STEEL waterproof IP68 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 264x115x174 mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Fitted with alibi memory, integrated on the motherboard.
- Functions available with DINI TOOLS utility
 - Configuration, calibration, data entry and print formatting.
 - Recording and filing of all the information on PC.
 - Complete retrieval of the saved data for quick replacement.
 - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e OIML or 3 x 3000e @ 0,3 $\mu\text{V/e}$ CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- 110-240 Vac power supply.
- Management of up to 4 independent scales (up to 2 for the AF03 version).
- Connectable with up to 16 analogue 350-Ohm (or 45 1000-Ohm) load cells.
- Connectable to printers and labellers with the command drivers.

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)

I/O SECTION

- Two RS232 serial ports, for connection to printer (in safety zone), PC or PLC.
- One RS232/RS485 serial port, for connection to printer (in safety zone), PC or PLC.
- 4 optoisolated outputs (16 in the IO versions).
- 2 optoisolated inputs (8 in the IO versions).
- Profibus interface to install in safety zone (available upon request for E-AF01 and E-BATCH1 versions).
- Analogue output with D/A converter at 16 bit, 0-10Vdc, 0-20mA, 4-20mA (available upon request for the IO versions).



www.diniargeo.com



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

interscale@yahoo.com

SALES AND TECHNICAL ASSISTANCE SERVICE