

# BENCH SCALE CI-200A + DLP

# CAS

## Numeric keys and 5 function keys

- 1) Set functions using numeric keys  
You can easily input numerals to set the functions of the CI-200A series indicator using the numeric keys.
- 2) Short cut keys  
With short cut keys (F1 & F2), you are able to switch quickly and easily to your preferred or mostly commonly used functions.



## Various power supplies

- The CI-200A series can be operated with a DC adaptor, rechargeable battery or dry battery (option). The ability to use a rechargeable battery or dry battery increases portability and allows the indicator to be used in environments where little or no power is available.



## FEATURES

- Strong mild steel construction
- Suitable for industrial environment
- 100% corner adjusted
- Simple and prompt full digital calibration
- High A/D conversion speed (80 times/sec)
- High resolution 1/10,000
- Multi-calibration
- Weight back-up function
- Weight Comparison: Hi, Low, OK (only LCD)
- Numeric keys & function keys
- Various power supplies [DC adaptor, Rechargeable battery or AA size dry battery x 6 (option)]
- 4 & 6 wire load cell support
- 2 serial ports
  - Standard: 1 port
  - Option: 1 additional port (for PC, Printer, Remote display communication, etc)
- Multi-purpose cradle
- Interface
  - Standard: RS-232C
  - Option: RS-422, RS-485

## OPTIONS

- DLP-50 Thermal Printer(Label printer)

## SPECIFICATIONS

Model	Bench scale CI-200A + DLP		
Platter size (cm)	30x40	40x50	50x60
Max. Capacity (kg)	30, 60, 100	60, 150, 250	100-500
Readability		5g, 10g, 20g	
A/D Internal resolution	1/520,000		
A/D External resolution	1/10,000		
Battery life	Approx. 120/33 hours		
Display	6 Segment 1 inch LED		
Power	DC 12V Adaptor & 6V rechargeable Pb Battery AA size dry battery x 6 ( Option )		
Operating Temp.	-10 °C ~ 40 °C		

