

# Floor Scale EXI 200AD series




## Features

- Explosion-proof, Dust explosion protection
- Water proof (IP66)
- Easy installation & repairing
- Accumulating function
- Sample rate(A/D conversion speed): 5~320 times/sec
- Resolution : 1/10,000
- Constant voltage touch method
- Use 4.3" Full Graphic TFT LCD
- Display many information (message, data)
- RS-485(Stream mode, Command Mode, MODBUS RTU)
- External I/O: - 2 Inputs / 4 outputs
- Analog output(0~20mA, 0~24mA, 4~20mA, 0~5V , 0~10V, ±5V, ±10V)
- Ethernet
- Full stainless steel 304 construction



## Front opening structure

- Easy installation & repairing



## Options

- RS-442/485 interface

## Specifications

Platform size (mm)	Capacity (kg)	Readability (kg)
1000 x 1000	1000	0.2
1200 x 1200	2000	0.5
1500 x 1500	2000	0.5
1500 x 1500	3000	1
1500 x 1500	5000	1
1500 x 2000	3000	1
1500 x 2000	5000	1
2000 x 2000	3000	1
2000 x 2000	5000	2
2000 x 3000	3000	1
2000 x 3000	5000	2

## Touch keypad

- Constant voltage touch method



## User-friendly Graphic interface(EXI-600AD)

- Use 4.3" Full Graphic TFT LCD
- Display many information (message, data)

