

## Product Details

### FEATURES:



- Capacity 20kg to 10t
- Forced by threaded connection
- High accuracy
- Alloy steel, stainless steel

### APPLICATION:

- Testing machine
- Crane scale
- Packing scale



### Wiring Diagram



### Outline Dimension:

Rated capacity	L	W	H	H1	T
20kg~150kg	70	12	64	24	M8
200kg~500kg	70	20	64	24	M12
700kg~1t	70	25	64	24	M12
1.2t~5t	88	32	90	38	M20
7.5t	88	40	90	38	M24
10t	110	50	110	46	M30X2

### SPECIFICATION:

Rated capacity: 20kg to 10ton	Operating temperature range: -30 to +70℃
Rated output: 2.0±0.003mv/v, 1.8±0.003mv/v(10t)	Maximum safe overload; 150% OF R.C
Accuracy class: 0.03	Ultimate safe overload; 200% OF R.C
Non-linearity: ±0.03% F.S	Recommended Excitation; 10 to 12V DC
Hysteresis error: ±0.03% F.S	Maximum Excitation; 15V DC
Non-repeatability: ±0.02% F.S	Environment protection: IP65(20kg~1t); IP67(1.2~10t)
Zero balance: ±1% F.S	Input impedance: 400±20Ω
Creep error(30minutes): ±0.03% F.S	Output impedance: 352±3Ω
Temperature effect on zero: ±0.02% F.S	Insulation resistance at 50V DC: ≥5000MΩ
Temperature effect on output: ±0.02% F.S	Material: nickel-plated alloy steel
Compensated temperature range: -10 to +40℃	Cable length: 2.6meter, diameter 5mm(20kg~1t; 3meter, diameter 6mm(1.2~7.5t); 3meter, diameter 5mm(10t)