



## ACCURATE ELECTRONIC BALANCE



# FSR-C

FUJITSU ELECTRIC CO., LTD



# ACCURATE ELECTRONIC BALANCE

## FSR-C



This is the Basic Precision balance 0,1g is the with the heavy duty design.  
Readability of this model easy to use and accurate

### % Percentage Weighing

Easier calculate the percentage of the weighing.



### Four Level Anti-Shock Adjustable Function



Very stable with adjustable feet.

### AC-DC available

Flexible power supply more than and low energy - consuming, 48 hours operation with dry cells.



### 17 Units Available : g, ct, lb, oz, ozt, GN, dwt...

A lot of weighing unit, all weighing units available here.



### Built with display temperature

Display the temperature area when weighing.



### Anti-Radiate, Anti-Static Metal Housing

Anti - electrostatic weighing stable even in radio transmission activity.



### Super size LCD display with backlight

Big LCD display, very easy to read, and readable in dark condition.



### All aluminium casting house

Heavy duty with aluminium case.



### Built in RS232

PC connection available, can connect to external display and also can connect to the external printer directly.



### Time & Date setting

Help us to record the weighing time & date. Also can print out the date and time on the print result.



### Weighing response time adjustable

user can adjust the speed of weigh response



### Counting and weighing

Faster counting with zero mistake.



### Animal weighing function

User for weigh the animal when moving, the weigh will keep stable.



### Dual Range

Depend on user's need. Can weigh more than expectation with the different readability.



### Built in under hook

This function is for underweighing, mostly for jewellery and gold



### Optional with rechargeable battery

This rechargeable battery is use for long time, suitable for un - electricity location.



### Optional with density weighing

The density can be measured in density mode, with under hook function.



## FSR-C



Item No.	Max Cap	Readability	Repeatability	Linearity	Work Temp	Pan Size	Housing Size
FSR-C2000	2000g/3000g	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C3000	3000g/5000g	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C6000	6000g/10kg	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm
FSR-C10000	10000g/15kg	0.1g/0.2g	±0.1g/±0.2g	±0.2g/±0.2g	10°C - 35°C	168x168mm	295x208x88mm

- Four level anti-Shock adjustable function
- Dual Range
- Anti-Radiate, Anti-Static Metal Housing
- Weighing Response time Adjustable
- 17 Units available : g, ct, lb, oz, GN, dwt...
- Counting and weighing
- AC-DC Available
- Built in Under Hook

- Super size LCD display with backlight
- Animal weighing function
- All Aluminium Casting Housing
- Built in RS232
- Time and Date Setting
- % Percentage weighing
- Built in display temperature
- Optional with density weighing
- Optional with rechargeable battery