

## DFWATEX2GDF

"DFWATEX2GDF": INDICATOR FOR DOSAGE IN ATEX 1 & 21 ZONES



Weight indicator for areas classified as hazardous with protection methods according to:

ATEX II 2(2)G Ex ib [ib Gb] IIC T4 Gb for gases,  
ATEX II 2(2)D Ex tb [ib Db] IIIC T197°C IP65 Db for dust.

Ideal for creating automatic or semiautomatic dosage systems in loading or in unloading, or multiproduct dosages and mixtures. EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

**PT.INTERSKALA MANDIRI INDONESIA**

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953  
interscale@yahoo.com

The best solution  
for advanced  
industrial  
applications

## MAIN FEATURES

- Waterproof 17-key numerical and functional keyboard.
- LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures, and icons for showing the active functions.
- IP68 Satin finish stainless steel case.
- Dimensions: 264x174x115mm.
- May be angled either to be set on a table or a wall.
- A/D 24-bit sigma-delta conversion with 4 channels, up to 200 conv./sec. autoselect.
- Management of a weighing system from 1 to 4 channels (cells) with digital equalization.
- Connectable with up to 4 analogue load cells with 350 Ohm input resistance.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 10.000e or multirange 2 x 3000e @ 0,3  $\mu\text{V/e}$  in CE-M approved version for legal for trade use.
- Calibration, Set-Up parameters, configurable from keyboard or PC with Dinitools.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Memory back-up for recording dosage data in case it's accidentally turned off.
- Printing the dosage and consumption data, en sure zone through fiber optic.
- Power supply through external power adapter PW200XRD, with PW200IO option.

## MAIN CERTIFICATIONS

- OIML R76

## I/O SECTION

- Fiber optic bidirectional port for connection with printer, labeller, PC, or PLC in safe area.
- 4 barriered logic digital outputs, with programmable function, for dosage system management, connectable to other intrinsic safety devices in a hazardous area.
- 4 inputs with functions dependents on the selected dosage function.



www.diniargeo.com



DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***PT.INTERSKALA MANDIRI INDONESIA***

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

[interscale@yahoo.com](mailto:interscale@yahoo.com)

**SALES AND TECHNICAL ASSISTANCE SERVICE**