

# DFWATEX3GD

DFW "ATEX3GD": WEIGHT INDICATOR FOR ATEX 2 & 22 ZONES



Weight indicator for areas classified as hazardous with protection methods according to:

ATEX II 3G Ex nR IIC T6 Gc X for gases

ATEX II 3D Ex tc IIIC T85°C Dc IP68 X for dust.

Ideal for creating weighing systems, batching, and automation systems. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

**PT. INTERSKALA MANDIRI INDONESIA**

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

[interscale@yahoo.com](mailto:interscale@yahoo.com)

The best solution  
for advanced  
industrial  
applications

## MAIN FEATURES

- Waterproof 17-key functional keypad.
- Backlit LCD display with 6 25-mm high contrast digits and with indication of active functions.
- IP68 Satin finish stainless steel case.
- Suitable for use on the table, or wall.
- Dimensions: 264x174x115mm.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu$ V/e in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions for internal factory use.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- Internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Board protection case inside the box.
- Digital calibration and set-up from keyboard.
- Instrument management & configuration from PC with DINITOOLS.
- 4 channels (for single weighing system).
- Power supply:
  - DFWATEX3GD: through 110-240Vac internal power adapter (optional power supply cable);
  - DFWATEX3GDB: through optional external battery (BP6ESTATEX3GD code), rechargeable in safe area. Battery charger not included.
- Connection with up to 8 load cells with 350 Ohm input resistance.

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76

## I/O SECTION

- RS232/C port configurable for connection to printer/labeller in safe zone.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, additional remote display, in safe zone.

## FUNCTIONS

- **KEYBOARD:**

Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, database of 30 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made.

- **SELECTABLE FUNCTIONS:**

- High Resolution Weighing x 10.
- Net/Gross or lb/kg conversion.
- Accumulation.
- Formula weighing.
- +/- Checkweighing.
- Percentage weighing.
- Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option).
- Counting(Max. resolution of 1.500.000 divisions).
- In/Out Truck weighing.
- Hold.
- Set Point Control (with DFIO option).



www.diniargeo.com



DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***PT.INTERSKALA MANDIRI INDONESIA***

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

[interscale@yahoo.com](mailto:interscale@yahoo.com)

**SALES AND TECHNICAL ASSISTANCE SERVICE**