

DFWLI\_2017

"DFWLI": MULTIFUNCTION WEIGHT INDICATOR, IN IP68 STAINLESS STEEL CASE



Easy to programme and use, versatile and high performing weight indicator. The wide range of available functions and interfaces, make it suitable for multiple industrial and commercial weighing applications, such as floor scales, mobile weighing, etc. Case in IP68 stainless steel. CE-M approvable (OIML R-76/EN 45501).

Working in cooperation with:

**PT. INTERSKALA MANDIRI INDONESIA**

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT -  
INDONESIA  
Tel. +62 21 555 1470 Fax. +6221 555 1953  
interscale@yahoo.com

The best solution  
for advanced  
industrial  
applications

## MAIN FEATURES:

- 5/17-key functional waterproof keypad, with indication for quick access to main functions and regulations.
- LCD 25mm backlit display with 6 high contrast digits and icons for indication of active functions.
- Waterproof IP68 STAINLESS STEEL case, with sealed rubber gasket, easy to clean and resistant in harsh and corrosive environments.
- Dimensions in mm: 243x145x78,4 mm.
- Suitable for use on the table, column, or wall.
- A/D 24 bit converter, 4 channels, up to 200 conv./sec. autoselect and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu\text{V/e}$  in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with built-in resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply 110-240 Vac.

## I/O SECTION

- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, remote display, and radio modem.  
Quick RJ RS232 plug connection.

## KEYBOARD FUNCTIONS

- Zeroing, Automatic tare, Presetable tare, printing and/or data transmission, selectable function command, on/off switching, backlit setting, function mode quick selection, user menu.

## MASTER/REPEATER OPTION

- Specific program (MSTSLV code) for use of the indicator as a universal weight repeater or as a multi-scale repeater (MASTER) in combination with DFW/DGT/MCW.

### FUNCTIONING MODES:

- Multi-scale repeater (MASTER):  
function which allows to repeat up to 32 independent scales, with the possibility of managing their functions, or displaying and printing the sum of the weighs of all the scales.
- UNIVERSAL weight repeater:  
function which allows to repeat the weight of any scales, through the configuration of the input string.

## AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Radiofrequency 6-key remote control: zero, tare, enable / disable function, print, switch-off.





www.diniargeo.com



DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

***PT.INTERSKALA MANDIRI INDONESIA***

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

interscale@yahoo.com

**SALES AND TECHNICAL ASSISTANCE SERVICE**