

EP3GD

Stainless steel scales "Easy Pesa 3GD" series, for ATEX zones 2 and 22



Fully stainless steel bench scales, for specific use in ATEX hazardous areas. Powered by a long lasting rechargeable battery which allows an easier installation directly where it's needed. These scales don't need a power supply socket in dangerous zone nor ATEX proof power supply cables. Provided with ATEX declaration of conformity. Ex II 3G IIC T6 Gc X and Ex II 3D IIIC T115°C Dc X.

Working in cooperation with:

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT -
INDONESIA
Tel. +62 21 555 1470 Fax. +6221 555 1953
interscale@yahoo.com

The best solution
for advanced
industrial
applications

PLATFORM FEATURES

- Approved "single point" STAINLESS STEEL load cell according to OIML R60 standards with protection against dust and water splashes according to IP67 standards.
- ATEX approved load cell with ATEX protection:
ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga.
ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65
- Structure, enclosure and loading plate made in AISI304 satin finish stainless steel.
- Adjustable levelling feet with plastic over shoe.
- Supplied with support column, height:
 - 500 mm in the "Q" models;
 - 700 mm in the "X" models.

WEIGHT INDICATOR FEATURES

- IP68 Weight indicator for ATEX areas with protection methods according to:
ATEX II 3G Ex nR IIC T6 Gc X for gases.
ATEX II 3D Ex tc IIIC T130°C Dc IP68 X for dust.
- EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501).
- Waterproof 17-key numerical and functional keyboard.
- Backlight LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Power supply through external battery pack with 100h operating time. It's possible to buy another battery pack for continuous use (24/7).
- Charger included in the supply.

SCALE FUNCTIONS

- SCALE FUNCTIONS
- Zeroing
- Automatic tare
- Presetable tare
- Selectable function command
- On/off switching.

SELECTABLE FUNCTIONING MODE

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weight totalization
- Formula weighing
- +/- Checkweighing
- Counting (Max. resolution of 1.500.000 divisions)

DETAIL 1



DETAIL 2





DETAIL 3



VERSIONS

Available versions

Codice	Piatto Max (mm)	Max (kg)	d (g)	 (g)*	 2R (g)*	d HR (g)*
EPQI3GD15B	400x400	15	2	5	2/5	1
EPQI3GD30B	400x400	30	5	10	5/10	2
EPQI3GD60B	400x400	60	10	20	10/20	5
EPQI3GD150B	400x400	150	20	50	20/50	10
<u>EPXI3GD60B</u>	600x600	60	10	20	10/20	5
<u>EPXI3GD150B</u>	600x600	150	20	50	20/50	10
<u>EPXI3GD300B</u>	600x600	300	50	100	50/100	20

(*) These divisions are obtainable only with the relative options



www.diniargeo.com



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

interscale@yahoo.com

SALES AND TECHNICAL ASSISTANCE SERVICE