

JB4QA

"JBQA": ATEX EQUALISED JUNCTION BOX, WITH UP TO 4 LOAD CELLS



IP67 junction box fitted with electronic board for junction and equalisation of 2, 3, or 4 load cells. Terminal boards with a screw for easing the connection of the load cells and the signal adjustment trimmer, for an accurate and reliable equalisation. Marking:

ATEX II 2G Ex ib IIC T6 Gb for gases.

ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

Working in cooperation with:

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953 interscale@yahoo.com

The best solution for advanced industrial applications

TECHNICAL FEATURES

- Case in ABS. Protection degree: IP67.
- Maximum input voltage: 24Vdc.
- Maximum input current: 700mA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Dimensions (lxwxh): 120x80x55mm.



"YOUR WORLDWIDE PARTNER FOR WEIGHING,

DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

interscale@yahoo.com

SALES AND TECHNICAL ASSISTANCE SERVICE