

TPWLKW

TPWLKW "LOGISTIC" SERIES PALLET TRUCK SCALE WITH WIDE FORKS



Pallet truck scale, with built-in electronic weighing, fitted with forks 680mm width, which making it ideal for the handling of pallets in the Food & Chemical Industry Sector. Fitted with rechargeable extractable battery. Available also with a built-in printer as well as CE-M DOUBLE RANGE approved. Manufactured, calibrated and adjusted in Italy by Dini Argeo, using certified sample masses.

Working in cooperation with:

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT -
 INDONESIA
 Tel. +62 21 555 1470 Fax. +6221 555 1953
interscale@yahoo.com

The best solution
 for advanced
 industrial
 applications

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Forks dimensions 1240 x 680 x 85 mm.
- Weighs about 134 kg.
- Structure in extra thick steel and oven-fire painted mechanics.
- Steering wheels and double loading poliurethane rollers.
- 4 stainless steel IP68 load cells for the legal for trade use version, IP67 load cells for the internal use version.
- Weight indicator in IP65 STAINLESS STEEL waterproof case, which is easy to clean and resistant to harsh and corrosive environments; large 25mm LCD display high contrast digits, which are clearly visible even in poor lighting conditions and with low temperatures, and 17-key functional waterproof keypad, with indication for quick access to main functions and regulations.
- Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.
- Power supply through extractable rechargeable battery mounted on the pallet truck column.
- The operating time is of about 80 hours of continuous use or one month with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function. Battery level indication.
- Equipped with 230Vac 50 Hz battery charger.
- Configurable RS232/C bidirectional port for connection to a printer, with customisable print format.
- Configurable RS232/C bidirectional port for PC, modem radio or portable terminal.
- IR input for remote control management.
- Fitted with thermal printer in the TPWLKWP and TPWLKWPM versions, with Date&Time card.

AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

SELECTABLE FUNCTION MODES




- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to Kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Piece counter
 - Hold

The “alibi memory” function is available in combination with the required operating mode and it is activated automatically when installing the relevant optional board.

- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

** These quick access keys to the menus can be blocked by configuring a dedicated password.*

VERSIONS

Available versions			
Codice	Max (kg)	d (kg)	 (kg)
TPWLKW-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKWP-2	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKWM-2 	1000 / 2000	--	0,5 / 1
TPWLKWPM-2 	1000 / 2000	--	0,5 / 1

Please take note that the column and the handle-bar require assembly.



www.diniargeo.com



DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano - Modena - Italy
Tel. +39.0536 843418

PT.INTERSKALA MANDIRI INDONESIA

GREEN SEDAYU BIZPARK, BLOK DM 11, N 62 - 11840 - KALIDERES, JAKARTA BARAT - INDONESIA

Tel. +62 21 555 1470 Fax. +6221 555 1953

interscale@yahoo.com

SALES AND TECHNICAL ASSISTANCE SERVICE