

CAS CI-200S WATER PROOF BENCH SCALE



All Stainless Steel Construction

It is available to use in watery environment because of all stainless steel load cell and indicator.

Waterproof Connector and Rechargeable Battery

It is available to use without power because of rechargeable battery and easy to attach power and communication cable by using waterproof connector.

FEATURES

- > All stainless steel construction
- > Stainless steel Load Cell & IP67 indicator
- > High visibility LCD display
- > Waterproof connector for RS-232 & Power cable
- > Bright comparator light- Yellow, Green, Red (only for CI200SC)
- > RS-232C interface
- > Comparator lamp (optional)

OPTIONS

- > RS-422/RS-485 interface
- > Printer: DEP-50 (ticket)
DLP-50 (label)

ICON



CI-200SC
+ Comparator lamp

SPECIFICATIONS

Model	CI-200S/SC								
Max.capacity (kg)	30	60	75	100	150	200	150	300	500
Readability (g)	5	10	10	10	20	20	50	50	100
Sign for status	STABLE, ZERO, TARE, G/N, BAT, HOLD, COM, kg/lb, UNDER, OK, OVER								
Display type	7-Segment 6digit LED (13w * 20H)/LED bar for weight comparison								
Operating temperature	-10°C ~ +40°C								
Power	DC 12V 1.5A Adapter/6V 5A Pb Rechargeable battery								
Key	10 Numeric keys & 5 Function keys								
Batter life	Approx. 30 hours								
Battety charging time	Approx. 12 hours								
Platter size (mm)	300 x 400			400 x 500			500 x 600		
Dimensions (mm)	500(L) x 300(W)x665(H)			610(L) x 400(W)x910(H)			780(L) x 500(W)x1050(H)		
Product weight (kg)	8			12			19.5		