

Indicator NT-580A

FEATURES

- > High micro processor
- > A/D conversion speed : 200times/sec
- > Watch-Dog circuitry (System restoration)
- > Weight Back-up
(Saving of weight at sudden power failure)
- > Various printer connection
- > External input: 6 relays
- > External output: 8 relays

APPLICATION

- > Measuring instrument tester, Automatic packer,
Platform scale, Truck scale, Packer scale,
Hopper scale, Limit scale

OPTIONS

- > RS-442/485 interface
- > Analog Output/BCD Output



Model		NT-580A
Load cell input voltage		DC 9V
Load cell connection (350 ohm)		8 L/C
Zero calibration		0.05 ~ 20 mV
Input sensitivity		1.2 μ V/D (OIML/NTEP/KS), 0.6 μ V/D (Non Approval)
A/D internal resolution		1/200,000
A/D external resolution		1/5,000 ~ 1/15,000
A/D Conversion speed		200times/sec
Display	Display type	VFD
	Digits	7 digits
Text size		13 mm
External		-
	Input function	6
	Out put function	8
Power	AC	SMPS (85V~265V)
	DC	-
	Rechargeable battery	-
Operating temperature		-10°C ~ +40°C
Dimension (WxDxH)mm		195x192x96
Product weight		2.5kg
IP class		-