



A1X Indicator

Introduction

Weighing indicator A1-X is widely applied in electronic platform scale, electronic floor scale and so on alike static weighing system equipped with 1~4 350Ω load cell.



Technical Parameter

- Simple operation
- Keyboard calibration and configuration
- Weighing up to 1:15,000 divisions
- Excitation voltage : DC 5V; Up to 4, 350 Ω load cells can be used
- Manual or automatic memory accumulation facility
- High Resolution (×10) Display
- Selectable digital filtering
- Selectable automatic power off
- 6-bit Display : 0.8 inches LED
- Selectable display resolution : 1 / 2 / 5 / 0.1 / 0.2 / 0.5 / 0.01 / 0.02 / 0.05 / 0.001 / 0.002 / 0.005 / 10 / 20 / 50 / 100 / 200 / 500 / 0.10 / 0.20 / 0.50 / 0.010 / 0.020 / 0.050
- RS-232C The interface , optional RS-485 interface 1200 2400 4800 9600 Baud rate continuous ASCII data output
- External Power supply : 230V(115V) AC. Internal rechargeable 6V DC Battery
- Operating temperature : 0°C to 40°C. Storage temperature: -25°C to 55°C
- Relative humidity : ≤ 85% non-condensing
- Dimensions : 256mm wide × 165mm high × 130mm deep