

Indicator NT-502A

FEATURES

- > 6 Wire load cell support
- > Single-pass automatic span calibration
- > Battery back-up
- > WATCH-DOG circuitry
- > RFI/EMI screened
- > Automatic zero tracking
- > Tare weight setting with ten key
- > RS-232C interface
- > Weight Back-up (Saving of weight at sudden power failure)

APPLICATION

- > Measuring instrument tester, Platform Scale, Truck Scale

OPTIONS

- > RS-442/485 interface
- > Analog Output/BCD in/Output

SPECIFICATIONS



Model		NT-502A
Load cell input voltage		DC 9V
Load cell connection (350 ohm)		8 L/C
Zero calibration		0.05 ~ 20 mV
Input sensitivity		1.2 μ V/D (OIML/NTEP/KS), 0.6 μ V/D (Non Approval)
A/D internal resolution		1/200,000
A/D external resolution		1/5,000 ~ 1/15,000
A/D Conversion speed		50times/sec
Display	Display type	VFD
	Digits	7 digits
Text size		13 mm
External		-
	Input function	4
	Out put function	4
Power	AC	AC 110/220V
	DC	-
	Rechargeable battery	-
Operating temperature		-10°C ~ +40°C
Dimension (WxDxH)mm		195x192x96
Product weight		2.5kg
IP class		-